



Description

Quantity	Unit
1	kg
2	kg
3	kg
4	kg
5	kg
6	kg
7	kg
8	kg
9	kg
10	kg
11	kg
12	kg
13	kg
14	kg
15	kg
16	kg
17	kg
18	kg
19	kg
20	kg
21	kg
22	kg
23	kg
24	kg
25	kg
26	kg
27	kg
28	kg
29	kg
30	kg
31	kg
32	kg
33	kg
34	kg
35	kg
36	kg
37	kg
38	kg
39	kg
40	kg
41	kg
42	kg
43	kg
44	kg
45	kg
46	kg
47	kg
48	kg
49	kg
50	kg
51	kg
52	kg
53	kg
54	kg
55	kg
56	kg
57	kg
58	kg
59	kg
60	kg
61	kg
62	kg
63	kg
64	kg
65	kg
66	kg
67	kg
68	kg
69	kg
70	kg
71	kg
72	kg
73	kg
74	kg
75	kg
76	kg
77	kg
78	kg
79	kg
80	kg
81	kg
82	kg
83	kg
84	kg
85	kg
86	kg
87	kg
88	kg
89	kg
90	kg
91	kg
92	kg
93	kg
94	kg
95	kg
96	kg
97	kg
98	kg
99	kg
100	kg

H-1 (2) 2X8 MIN.

H-2 (2) 2X10 MIN.

H-3 (2) 1 3/4" X 11 7/8" LVL'S MIN.

H-4 (2) 1 3/4" X 14" LVL'S MIN.

H-5 (2) 1 3/4" X 16" LVL'S MIN.

HEADERS WITHOUT NOTE ARE MIN. DOUBLE
2X6. PROVIDE 2X6 TOP AND BOTTOM PLATE
FOR ALL HEADERS AND (1) JACK STUD AND (1)
FULL HEIGHT KING STUD AT EACH JAMB.

- (L1) GALVANIZED L-4x4x5/16" BRICK LEDGER
ANGLE W/ 8" BEARING AT EACH END.
- (L2) GALVANIZED L-6x4x5/16" (LONG LEG
VERTICAL) BRICK LEDGER ANGLE W/ 8"
BEARING AT EACH END.
- (L3) GALVANIZED L-1x4x3/8" (LONG LEG
VERTICAL) BRICK LEDGER ANGLE W/ 12"
BEARING AT EACH END.
- (L4) GALVANIZED L-6x4x5/16" (LONG LEG
VERTICAL) BRICK LEDGER ANGLE W/
PAIRS OF SIMPSON SD5-25000 WOOD
SCREWS AT 3' GAGE AT 16" O.C.

PAD FOOTINGS (LXWXD)	RE-INFORCING
----------------------	--------------

WALL FOOTINGS (LXWXD)		RE-INFORCING
WF-1	CONT. XI'-4"XB"	2 - #4 CONT. @ 9 1/2" O.C.

1702 SOUTH 150 AVE. OMAHA, NEBRASKA 68144

PLAN DATE
07/17/2006

15-2510

100

A1 01

THESE PLANS ARE SPECIFICALLY
DESIGNED FOR CONSTRUCTION BY
MCNEIL COMPANY AND ARE
NOT TO BE USED FOR ANY OTHER PURPOSE.
REPLICATION OF THESE PLANS IN
WHOLE OR PART WITHOUT WRITTEN
CONSENT FROM MCNEIL COMPANY
IS PROHIBITED.