



Contract - Detailed

Pella Window and Door Showroom of Omaha

14478 Crest Rd.

Omaha, NE 68138

Phone: (402) 331-9225 Fax: (402) 331-3076

Sales Rep Name: Drobny, Brian

Sales Rep Phone: (402) 660-7148

Sales Rep Fax:

Sales Rep E-Mail: briandrobny@pellaomaha.com


Customer Information	Project/Delivery Address	Order Information
McNeil Company Builders 4666 S 132nd Street OMAHA, NE 68137 Primary Phone: Mobile Phone: Fax Number: (402) 3330182 E-Mail: accounting@mcneilcompany.com Contact Name: Great Plains #: MCNEILBLDR Customer Number: 1002066689 Customer Account: 1000228280	1702 S 150th Ave/Crockett/McNeil Company Builders 1702 S 150th Ave Lot # Lot 22 Heartwood WEST OMAHA, NE 68144 County: DOUGLAS Owner Name: Owner Phone:	Quote Name: Iron Ore Reserve Contemporary 9/9/26 Order Number: 230 Quote Number: 21290375 Order Type: Installed Sales Wall Depth: Payment Terms: Net 30 Days Tax Code: USETAX Cust Delivery Date: None Quoted Date: 9/9/2026 Contracted Date: Booked Date: Customer PO #:
Accessories Managed / Delivery Date		
Door Handles	1/1/0001	Hinge & Sliding Door Screens
	1/1/0001	Window Screens
	1/1/0001	Window Hardware
	1/1/0001	

Customer Notes: RESERVE CONTEMPORARY SERIES

Iron Ore Exterior
Unfinished Interior
Champagne Hardware
Champagne Screen Frames
Satin Nickel Door Hardware
Advanced Low-E Glass
7/8" ILT Grilles

Full Pella Install, Zip wall

Line #	Location:	Attributes		
10	LL Fitness Room	Pella Reserve, Contemporary 2-Wide Casement, 64 X 53, Iron Ore		
			Item Price	Qty
			\$2,169.48	1
				Ext'd Price
				\$2,169.48



PK #
2245

Viewed From Exterior

1: 3253 Left Casement
Frame Size: 32 X 53
General Information: Crank Out, Standard, Clad, Pine, 5", 3 11/16"
Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore
Interior Color / Finish: Unfinished Interior
Sash / Panel: Square, Square, Standard, 1.46, 1.46, 1.46
Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude
Hardware Options: Wash Hinge Hardware, Saldo Fold-Away Crank, Champagne, No Window Opening Control Device, No Limited Opening Hardware, No Integrated Sensor, Shipped Separate, Accessory Managed
Screen: Full Screen, Champagne, InView™, Shipped Separate, Accessory Managed
Performance Information: U-Factor 0.29, SHGC 0.25, VLT 0.46, CPD PEL-N-11-24315-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, FPA FL31311, STC 26, OITC 23, Clear Opening Width 22.25, Clear Opening Height 48.875, Clear Opening Area 7.551867, Egress Meets minimum clear opening and 5.7 sq.ft
Grille: ILT, No Custom Grille, 7/8", Traditional (2W3H), Square, Square

2: 3253 Fixed Sash Set
Frame Size: 32 X 53
General Information: Standard, Clad, Pine, 5", 3 11/16"
Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore
Interior Color / Finish: Unfinished Interior
Sash / Panel: Square, Square, Standard, 1.46, 1.46, 1.46
Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude
Performance Information: U-Factor 0.28, SHGC 0.28, VLT 0.51, CPD PEL-N-1-59313-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, FPA FL31312
Grille: ILT, No Custom Grille, 7/8", Traditional (2W3H), Square, Square
Vertical Mull 1: FactoryMull, Standard Joining Mullion, Frame To Frame Width- 0", Mull Design Pressure- 20
Wrapping Information: Foldout Fins, Factory Applied, No Head Drip Cap, No Exterior Trim, 3-11/16", 5", Factory Applied, Manufacturer Recommended Clearance, Perimeter Length = 234".

Rough Opening: 64 - 3/4" X 53 - 3/4"

Customer Notes: COMPOSITE COMES WITH NO JAMB EXTENSION

21DRINST0050 - A - Window Install Per LF - NCI - Whole House

Qty 20


21DRINST1000 - F - ADDER - Zip Tape Install Per LF - NCI

Qty 20

Line #	Location:	Attributes				
15	LL Family Bar	32" 53" Viewed From Exterior	Pella Reserve, Contemporary Sash Set, Fixed, 32 X 53, Iron Ore 1: 3253 Fixed Sash Set Frame Size: 32 X 53 General Information: Standard, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Sash / Panel: Square, Square, Standard, 1.46, 1.46, 1.46 Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Performance Information: U-Factor 0.27, SHGC 0.30, VLT 0.57, CPD PEL-N-1-59311-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, FPA FL31312 Grille: No Grille, Wrapping Information: Steady Set - Interior Install, Factory Applied, No Exterior Trim, 6-9/16", 7 7/8", Standard Four Sided Jamb Extension, Factory Applied, 2x6 Bracket, Manufacturer Recommended Clearance, Perimeter Length = 170".	Item Price \$862.08	Qty 1	Ext'd Price \$862.08
	PK # 2245					

Rough Opening: 32 - 3/4" X 53 - 3/4"

21DRINST0050 - A - Window Install Per LF - NCI - Whole House	Qty	15
21DRINST1000 - F - ADDER - Zip Tape Install Per LF - NCI	Qty	15

Line #	Location:	Attributes			
20	LL Family Door	Pella Reserve, Double Sliding Door, Fixed / Vent Left, 95.25 X 95.5, Iron Ore	Item Price	Qty	Ext'd Price
		1: 9696 Fixed / Vent Left Double Sliding Door Frame Size: 95 1/4 X 95 1/2 General Information: Factory Assembled, Standard, Clad, Pine, 5 7/8", 4 9/16" Exterior Color / Finish: Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Sash / Panel: Square, Square, Standard Glass: Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Frame Selection: Wood Trim Cover, Factory Applied, Jamb Covers Included Hardware Options: Vent Lock, Black, Keylock Included, Plazo, Handle Included, Handle Included, Satin Nickel, Satin Nickel, Shipped Separate, Accessory Managed, Random, Chrome, No Integrated Sensor Screen: Sliding Screen, Iron Ore, Black, InView™ , Shipped Separate, Accessory Managed Performance Information: U-Factor 0.30, SHGC 0.28, VLT 0.51, CPD PEL-N-304-00155-00001, Performance Class LC, PG 35, Calculated Positive DP Rating 35, Calculated Negative DP Rating 35, FPA FL47325, STC 28, OITC 24 Grille: No Grille, Wrapping Information: Foldout Fins, Factory Applied, No Exterior Trim, 6-9/16", Factory Supplied, Shipped Separately, Manufacturer Recommended Clearance, Perimeter Length = 382".	\$5,606.75	1	\$5,606.75
	PK # 2245				
	Viewed From Exterior				

Rough Opening: 96" X 96"

21DRINST0200 - C - 2 Panel Door per LF - NCI - Whole House	Qty	32
21DRINST1000 - F - ADDER - Zip Tape Install Per LF - NCI	Qty	32

Line #	Location:	Attributes				
25	LL Family Room	32" 53" PK # 2245 Viewed From Exterior	Pella Reserve, Contemporary Sash Set, Fixed, 32 X 53, Iron Ore 1: 3253 Fixed Sash Set Frame Size: 32 X 53 General Information: Standard, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Sash / Panel: Square, Square, Standard, 1.46, 1.46, 1.46 Glass: Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Performance Information: U-Factor 0.28, SHGC 0.28, VLT 0.51, CPD PEL-N-1-59313-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, FPA FL31312, STC 28, OITC 24 Grille: ILT, No Custom Grille, 7/8", Traditional (2W3H), Square, Square Wrapping Information: Steady Set - Interior Install, Factory Applied, No Exterior Trim, 6-9/16", 7 7/8", Standard Four Sided Jamb Extension, Factory Applied, 2x6 Bracket, Manufacturer Recommended Clearance, Perimeter Length = 170".	Item Price \$1,239.05	Qty 3	Ext'd Price \$3,717.15

Rough Opening: 32 - 3/4" X 53 - 3/4"

21DRINST0050 - A - Window Install Per LF - NCI - Whole House

Qty 15

21DRINST1000 - F - ADDER - Zip Tape Install Per LF - NCI

Qty 15

Line #	Location:	Attributes				
30	LL Game Area	PK # 2245 Viewed From Exterior <td> 1: 3253 Fixed Sash Set Frame Size: 32 X 53 General Information: Standard, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Sash / Panel: Square, Square, Standard, 1.46, 1.46, 1.46 Glass: Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Performance Information: U-Factor 0.28, SHGC 0.28, VLT 0.51, CPD PEL-N-1-59313-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, FPA FL31312, STC 28, OITC 24 Grille: ILT, No Custom Grille, 7/8", Traditional (2W3H), Square, Square 2: 3253 Fixed Sash Set Frame Size: 32 X 53 General Information: Standard, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Sash / Panel: Square, Square, Standard, 1.46, 1.46, 1.46 Glass: Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Performance Information: U-Factor 0.28, SHGC 0.28, VLT 0.51, CPD PEL-N-1-59313-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, FPA FL31312, STC 28, OITC 24 Grille: ILT, No Custom Grille, 7/8", Traditional (2W3H), Square, Square Vertical Mull 1: FactoryMull, Standard Joining Mullion, Frame To Frame Width- 0", Mull Design Pressure- 20 Wrapping Information: Steady Set - Interior Install, Factory Applied, No Head Drip Cap, No Exterior Trim, 6-9/16", 7 7/8", Standard Four Sided Jamb Extension, Factory Applied, 2x6 Bracket, Manufacturer Recommended Clearance, Perimeter Length = 234". </td> <td> Item Price \$2,446.72 </td> <td> Qty 1 </td> <td> Ext'd Price \$2,446.72 </td>	1: 3253 Fixed Sash Set Frame Size: 32 X 53 General Information: Standard, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Sash / Panel: Square, Square, Standard, 1.46, 1.46, 1.46 Glass: Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Performance Information: U-Factor 0.28, SHGC 0.28, VLT 0.51, CPD PEL-N-1-59313-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, FPA FL31312, STC 28, OITC 24 Grille: ILT, No Custom Grille, 7/8", Traditional (2W3H), Square, Square 2: 3253 Fixed Sash Set Frame Size: 32 X 53 General Information: Standard, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Sash / Panel: Square, Square, Standard, 1.46, 1.46, 1.46 Glass: Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Performance Information: U-Factor 0.28, SHGC 0.28, VLT 0.51, CPD PEL-N-1-59313-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, FPA FL31312, STC 28, OITC 24 Grille: ILT, No Custom Grille, 7/8", Traditional (2W3H), Square, Square Vertical Mull 1: FactoryMull, Standard Joining Mullion, Frame To Frame Width- 0", Mull Design Pressure- 20 Wrapping Information: Steady Set - Interior Install, Factory Applied, No Head Drip Cap, No Exterior Trim, 6-9/16", 7 7/8", Standard Four Sided Jamb Extension, Factory Applied, 2x6 Bracket, Manufacturer Recommended Clearance, Perimeter Length = 234".	Item Price \$2,446.72	Qty 1	Ext'd Price \$2,446.72

Rough Opening: 64 - 3/4" X 53 - 3/4"

21DRINST0050 - A - Window Install Per LF - NCI - Whole House

Qty 20

21DRINST1000 - F - ADDER - Zip Tape Install Per LF - NCI

Qty 20

Line #	Location:	Attributes
--------	-----------	------------

35 LL Game Area

Pella Reserve, Contemporary 3-Wide Sash Set, 96 X 21, Iron OreItem PriceQtyExt'd Price

\$1,889.98

1

\$1,889.98



PK #

2245

Viewed From Exterior

1: 3221 Fixed Sash Set**Frame Size:** 32 X 21**General Information:** Standard, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Iron Ore**Interior Color / Finish:** Unfinished Interior**Sash / Panel:** Square, Square, Standard, 1.46, 1.46, 1.46**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Performance Information:** U-Factor 0.27, SHGC 0.30, VLT 0.57, CPD PEL-N-1-59311-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, FPA FL31312**Grille:** No Grille,**2: 3221 Fixed Sash Set****Frame Size:** 32 X 21**General Information:** Standard, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Iron Ore**Interior Color / Finish:** Unfinished Interior**Sash / Panel:** Square, Square, Standard, 1.46, 1.46, 1.46**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Performance Information:** U-Factor 0.27, SHGC 0.30, VLT 0.57, CPD PEL-N-1-59311-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, FPA FL31312**Grille:** No Grille,**3: 3221 Fixed Sash Set****Frame Size:** 32 X 21**General Information:** Standard, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Iron Ore**Interior Color / Finish:** Unfinished Interior**Sash / Panel:** Square, Square, Standard, 1.46, 1.46, 1.46**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Performance Information:** U-Factor 0.27, SHGC 0.30, VLT 0.57, CPD PEL-N-1-59311-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, FPA FL31312**Grille:** No Grille,**Vertical Mull 1:** FactoryMull, Standard Joining Mullion, Frame To Frame Width- 0", Mull Design Pressure- 20**Vertical Mull 2:** FactoryMull, Standard Joining Mullion, Frame To Frame Width- 0", Mull Design Pressure- 20**Wrapping Information:** Foldout Fins, Factory Applied, No Head Drip Cap, No Exterior Trim, 3-11/16", 5", Factory Applied, Manufacturer Recommended Clearance, Perimeter Length = 234".**Rough Opening:** 96 - 3/4" X 21 - 3/4"

Customer Notes: COMPOSITE COMES WITH NO JAMB EXTENSION (VERIFY)

21DRINST0050 - A - Window Install Per LF - NCI - Whole House

Qty 20

21DRINST1000 - F - ADDER - Zip Tape Install Per LF - NCI

Qty 20

Line #	Location:	Attributes				
40	Garage Front	65" 32" Viewed From Exterior	Pella Reserve, Contemporary Sash Set, Fixed, 32 X 65, Iron Ore 1: 3265 Fixed Sash Set Frame Size: 32 X 65 General Information: Standard, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Sash / Panel: Square, Square, Standard, 1.46, 1.46, 1.46 Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Performance Information: U-Factor 0.28, SHGC 0.28, VLT 0.51, CPD PEL-N-1-59313-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, FPA FL31312, STC 28, OITC 24 Grille: ILT, No Custom Grille, 7/8", Traditional (2W4H), Square, Square Wrapping Information: Steady Set - Interior Install, Factory Applied, No Exterior Trim, 6-9/16", 7 7/8", Standard Four Sided Jamb Extension, Factory Applied, 2x6 Bracket, Manufacturer Recommended Clearance, Perimeter Length = 194".	Item Price \$1,319.84	Qty 1	Ext'd Price \$1,319.84

Viewed From Exterior

Rough Opening: 32 - 3/4" X 65 - 3/4"

21DRINST0050 - A - Window Install Per LF - NCI - Whole House

Qty 17

21DRINST1000 - F - ADDER - Zip Tape Install Per LF - NCI

Qty 17

Line #	Location:	Attributes		
45	Garage Front			


Rough Opening: 64 - 3/4" X 86 - 3/4"

21DRINST0050 - A - Window Install Per LF - NCI - Whole House

Qty 26


21DRINST1000 - F - ADDER - Zip Tape Install Per LF - NCI

Qty 26

Line #	Location:	Attributes							
50	Front Entry Door	 Frame Radius = 46.5066 PK # 2245 Viewed From Exterior	Pella Reserve, Traditional Double Inswing Door, Active / Passive Arch Head, 75 X 107.5, Iron Ore 1: 75107.5 Active / Passive Double Inswing Door Arch Head Frame Size: 75 X 107 1/2 X 88 1/2 General Information: Standard, Clad, Pine, 7 7/8", 6 9/16", Standard Sill, Black Finish Sill, Black Composite Threshold Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Sash / Panel: Ogee, Ogee, Custom, 8.125, 4.6875, 4.6875, 6", Clad Panel Glass: Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Hardware Options: Spiere, Satin Nickel, Order Handle Set, Shipped Separate, Multipoint Lock, No Integrated Sensor Performance Information: CPD Not Rated, FPA None Grille: No Grille, Wrapping Information: Foldout Fins, Factory Applied, No Exterior Trim, 6-9/16", 7 7/8", Factory Applied, Manufacturer Recommended Clearance, Perimeter Length = 340", Glazing Pressure = 195. <table><tr><th>Item Price</th><th>Qty</th><th>Ext'd Price</th></tr><tr><td>\$11,898.27</td><td>1</td><td>\$11,898.27</td></tr></table>	Item Price	Qty	Ext'd Price	\$11,898.27	1	\$11,898.27
Item Price	Qty	Ext'd Price							
\$11,898.27	1	\$11,898.27							


Rough Opening: 75 - 3/4" X 108"

21DRINST0200 - C - 2 Panel Door per LF - NCI - Whole House	Qty	31
21DRINST1000 - F - ADDER - Zip Tape Install Per LF - NCI	Qty	31

Line #	Location:	Attributes								
55	Head Drip Fin	 Frame Radius = 46.5066 PK # 2245 Viewed From Exterior	Head Drip Fin, Arch Head, 75 X 107.5	<table><tr><th>Item Price</th><th>Qty</th><th>Ext'd Price</th></tr><tr><td>\$398.21</td><td>1</td><td>\$398.21</td></tr></table>	Item Price	Qty	Ext'd Price	\$398.21	1	\$398.21
Item Price	Qty		Ext'd Price							
\$398.21	1	\$398.21								
		1: 75107.5 Active / Passive Double Inswing Door Arch Head Frame Size: 75 X 107 1/2 X 88 1/2 General Information: Clad, Pine, 7 7/8", 6 9/16", Black Composite Threshold Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Wrapping Information: Exterior Trim Options, Head Drip Fin, 7 7/8", Perimeter Length = 340", Glazing Pressure = 195.								

Rough Opening: 75 - 3/4" X 108"

Line #	Location:	Attributes		
60	Contemplation Study	Pella Reserve, Contemporary 2-Wide Sash Set, Pella Reserve, 2-Wide Sash Set, 64 X 86, Iron Ore 1: 3265 Fixed Sash Set Frame Size: 32 X 65 General Information: Standard, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Sash / Panel: Square, Square, Standard, 1.46, 1.46, 1.46 Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Performance Information: U-Factor 0.28, SHGC 0.28, VLT 0.51, CPD PEL-N-1-59313-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, FPA FL31312, STC 28, OITC 24 Grille: ILT, No Custom Grille, 7/8", Traditional (2W4H), Square, Square 2: 3265 Fixed Sash Set Frame Size: 32 X 65 General Information: Standard, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Sash / Panel: Square, Square, Standard, 1.46, 1.46, 1.46 Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Performance Information: U-Factor 0.28, SHGC 0.28, VLT 0.51, CPD PEL-N-1-59313-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, FPA FL31312, STC 28, OITC 24 Grille: ILT, No Custom Grille, 7/8", Traditional (2W4H), Square, Square 3: 3221 Fixed Sash Set Frame Size: 32 X 21 General Information: Standard, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Sash / Panel: Square, Square, Standard, 1.46, 1.46, 1.46 Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Performance Information: U-Factor 0.28, SHGC 0.28, VLT 0.51, CPD PEL-N-1-59313-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, FPA FL31312 Grille: ILT, No Custom Grille, 7/8", Traditional (2W1H), Square, Square 4: 3221 Fixed Sash Set Frame Size: 32 X 21 General Information: Standard, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Sash / Panel: Square, Square, Standard, 1.46, 1.46, 1.46 Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Performance Information: U-Factor 0.28, SHGC 0.28, VLT 0.51, CPD PEL-N-1-59313-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, FPA FL31312 Grille: ILT, No Custom Grille, 7/8", Traditional (2W1H), Square, Square Horizontal Mull 1: FactoryMull, Reinforcing Plate, Frame To Frame Width- 0", Mull Design Pressure- 20, Overall Thru Direction- Horizontal Vertical Mull 1: FactoryMull, Standard Joining Mullion, Frame To Frame Width- 0", Mull Design Pressure- 20, Overall Thru Direction- Horizontal Vertical Mull 2: FactoryMull, Standard Joining Mullion, Frame To Frame Width- 0", Mull Design Pressure- 20, Overall Thru Direction- Horizontal Wrapping Information: Steady Set - Interior Install, Factory Applied, No Head Drip Cap, No Exterior Trim, 6-9/16", 7 7/8", Standard Four Sided Jamb Extension, Factory Applied, 2x6 Bracket, Manufacturer Recommended Clearance, Perimeter Length = 300".		
			Item Price	Qty
			\$4,252.99	1
				Ext'd Price
				\$4,252.99



PK #
2245

Viewed From Exterior

Rough Opening: 64 - 3/4" X 86 - 3/4"

21DRINST1000 - F - ADDER - Zip Tape Install Per LF - NCI

Qty 26

21DRINST0050 - A - Window Install Per LF - NCI - Whole House

Qty 26

For more information regarding the finishing, maintenance, service and warranty of all Pella® products, visit the Pella® website at www.pella.com

Line #	Location:	Attributes			
65	Master WRDB				

Rough Opening: 32 - 3/4" X 65 - 3/4"

21DRINST0050 - A - Window Install Per LF - NCI - Whole House

Qty 17

21DRINST1000 - F - ADDER - Zip Tape Install Per LF - NCI

Qty 17

Line #	Location:	Attributes			
70	Master Bath T.C.	Viewed From Exterior PK # 2245 Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior Viewed From Exterior			


Rough Opening: 25 - 3/4" X 41 - 3/4"


21DRINST0050 - A - Window Install Per LF - NCI - Whole House

Qty 12

21DRINST1000 - F - ADDER - Zip Tape Install Per LF - NCI

Qty 12

Line #	Location:	Attributes		
75	Master Bath Tub	Pella Reserve, Contemporary 2-Wide Sash Set, 64 X 73, Iron Ore	Item Price	Qty
			\$3,069.75	1
				Ext'd Price
				\$3,069.75
	 PK # 2245 Viewed From Exterior	1: 3273 Fixed Sash Set Frame Size: 32 X 73 General Information: Standard, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Sash / Panel: Square, Square, Standard, 1.46, 1.46, 1.46 Glass: Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Performance Information: U-Factor 0.28, SHGC 0.28, VLT 0.51, CPD PEL-N-1-59313-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, FPA FL31312, STC 28, OITC 24 Grille: ILT, No Custom Grille, 7/8", Traditional (2W4H), Square, Square 2: 3273 Fixed Sash Set Frame Size: 32 X 73 General Information: Standard, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Sash / Panel: Square, Square, Standard, 1.46, 1.46, 1.46 Glass: Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Performance Information: U-Factor 0.28, SHGC 0.28, VLT 0.51, CPD PEL-N-1-59313-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, FPA FL31312, STC 28, OITC 24 Grille: ILT, No Custom Grille, 7/8", Traditional (2W4H), Square, Square Vertical Mull 1: FactoryMull, Standard Joining Mullion, Frame To Frame Width- 0", Mull Design Pressure- 20 Wrapping Information: Steady Set - Interior Install, Factory Applied, No Head Drip Cap, No Exterior Trim, 6-9/16", 7 7/8", Standard Four Sided Jamb Extension, Factory Applied, 2x6 Bracket, Manufacturer Recommended Clearance, Perimeter Length = 274".		
	Rough Opening: 64 - 3/4" X 73 - 3/4"			
	21DRINST0050 - A - Window Install Per LF - NCI - Whole House	Qty	24	
	21DRINST1000 - F - ADDER - Zip Tape Install Per LF - NCI	Qty	24	

Line #	Location:	Attributes					
80	Master Bed		PK # 2245	Pella Reserve, Contemporary Casement Left, 32 X 65, Iron Ore 1: 3265 Left Casement Frame Size: 32 X 65 General Information: Crank Out, Standard, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Sash / Panel: Square, Square, Standard, 1.46, 1.46, 1.46 Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Hardware Options: Wash Hinge Hardware, Saldo Fold-Away Crank, Champagne, No Window Opening Control Device, No Limited Opening Hardware, No Integrated Sensor, Shipped Separate, Accessory Managed Screen: Full Screen, Champagne, InView™, Shipped Separate, Accessory Managed Performance Information: U-Factor 0.29, SHGC 0.27, VLT 0.51, CPD PEL-N-11-24313-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, FPA FL31311, STC 26, OITC 23, Clear Opening Width 22.25, Clear Opening Height 60.875, Clear Opening Area 9.406033, Egress Meets minimum clear opening and 5.7 sq.ft Grille: No Grille, Wrapping Information: Steady Set - Interior Install, Factory Applied, No Exterior Trim, 6-9/16", 7 7/8", Standard Four Sided Jamb Extension, Factory Applied, 2x6 Bracket, Manufacturer Recommended Clearance, Perimeter Length = 194".	Item Price \$1,116.02	Qty 1	Ext'd Price \$1,116.02
Viewed From Exterior							
Rough Opening: 32 - 3/4" X 65 - 3/4"							
21DRINST0050 - A - Window Install Per LF - NCI - Whole House						Qty	17
21DRINST1000 - F - ADDER - Zip Tape Install Per LF - NCI						Qty	17

Line #	Location:	Attributes				
85	Master Bed	 Viewed From Exterior	Pella Reserve, Contemporary Casement Right, 32 X 65, Iron Ore	Item Price	Qty	Ext'd Price
			\$1,116.02	1	\$1,116.02	
	PK # 2245	1: 3265 Right Casement Frame Size: 32 X 65 General Information: Crank Out, Standard, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Sash / Panel: Square, Square, Standard, 1.46, 1.46, 1.46 Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Hardware Options: Wash Hinge Hardware, Saldo Fold-Away Crank, Champagne, No Window Opening Control Device, No Limited Opening Hardware, No Integrated Sensor, Shipped Separate, Accessory Managed Screen: Full Screen, Champagne, InView™, Shipped Separate, Accessory Managed Performance Information: U-Factor 0.29, SHGC 0.27, VLT 0.51, CPD PEL-N-11-24313-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, FPA FL31311, STC 26, OITC 23, Clear Opening Width 22.25, Clear Opening Height 60.875, Clear Opening Area 9.406033, Egress Meets minimum clear opening and 5.7 sq.ft Grille: No Grille, Wrapping Information: Steady Set - Interior Install, Factory Applied, No Exterior Trim, 6-9/16", 7 7/8", Standard Four Sided Jamb Extension, Factory Applied, 2x6 Bracket, Manufacturer Recommended Clearance, Perimeter Length = 194".				
Rough Opening: 32 - 3/4" X 65 - 3/4"						
21DRINST0050 - A - Window Install Per LF - NCI - Whole House			Qty	17		
21DRINST1000 - F - ADDER - Zip Tape Install Per LF - NCI			Qty	17		

Line #	Location:	Attributes			
90	Master Bed	71" 25" Viewed From Exterior PK # 2245 1: 2571 Fixed Sash Set Frame Size: 25 X 71 General Information: Standard, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Sash / Panel: Square, Square, Standard, 1.46, 1.46, 1.46 Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Performance Information: U-Factor 0.27, SHGC 0.30, VLT 0.57, CPD PEL-N-1-59311-00001, Performance Class CW, PG 35, Calculated Positive DP Rating 35, Calculated Negative DP Rating 35, FPA FL31312 Grille: No Grille, Wrapping Information: Steady Set - Interior Install, Factory Applied, No Exterior Trim, 6-9/16", 7 7/8", Standard Four Sided Jamb Extension, Factory Applied, 2x6 Bracket, Manufacturer Recommended Clearance, Perimeter Length = 192". Item Price Qty Ext'd Price \$940.67 3 \$2,822.01 </			


Rough Opening: 25 - 3/4" X 71 - 3/4"

21DRINST0050 - A - Window Install Per LF - NCI - Whole House

Qty 17

21DRINST1000 - F - ADDER - Zip Tape Install Per LF - NCI

Qty 17

Line #	Location:	Attributes				
95	Great Room	 PK # 2245 Viewed From Exterior	Pella Reserve, Contemporary Sash Set, Pella Reserve, Sash Set, 32 X 102, Iron Ore	Item Price \$2,261.08	Qty 3	Ext'd Price \$6,783.24
1: 3273 Fixed Sash Set Frame Size: 32 X 73 General Information: Standard, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Sash / Panel: Square, Square, Standard, 1.46, 1.46, 1.46 Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Performance Information: U-Factor 0.28, SHGC 0.28, VLT 0.51, CPD PEL-N-1-59313-00001, Performance Class CW, PG 45, Calculated Positive DP Rating 45, Calculated Negative DP Rating 45, FPA FL31312, STC 28, OITC 24 Grille: ILT, No Custom Grille, 7/8", Traditional (2W4H), Square, Square 2: 3229 Fixed Sash Set Frame Size: 32 X 29 General Information: Standard, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Sash / Panel: Square, Square, Standard, 1.46, 1.46, 1.46 Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Performance Information: U-Factor 0.28, SHGC 0.28, VLT 0.51, CPD PEL-N-1-59313-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, FPA FL31312 Grille: ILT, No Custom Grille, 7/8", Traditional (2W2H), Square, Square Horizontal Mull 1: FactoryMull, Standard Joining Mullion, Frame To Frame Width- 0", Mull Design Pressure- 20 Wrapping Information: Steady Set - Interior Install, Factory Applied, No Exterior Trim, 6-9/16", 7 7/8", Standard Four Sided Jamb Extension, Factory Applied, 2x6 Bracket, Manufacturer Recommended Clearance, Perimeter Length = 268".						

Rough Opening: 32 - 3/4" X 102 - 3/4"

21DRINST0050 - A - Window Install Per LF - NCI - Whole House


Qty 23

21DRINST1000 - F - ADDER - Zip Tape Install Per LF - NCI

Qty 23

Line #	Location:	Attributes
--------	-----------	------------

100 Dining Room



PK #

2245

Viewed From Exterior

Pella Reserve, Contemporary 2-Wide Sash Set, 64 X 65, Iron OreItem PriceQtyExt'd Price

\$2,664.15

1

\$2,664.15

1: 3265 Fixed Sash Set**Frame Size:** 32 X 65**General Information:** Standard, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Iron Ore**Interior Color / Finish:** Unfinished Interior**Sash / Panel:** Square, Square, Standard, 1.46, 1.46, 1.46**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.51, CPD PEL-N-1-59313-00001, Performance Class CW, PG 50, Calculated Positive DP

Rating 50, Calculated Negative DP Rating 50, FPA FL31312, STC 28, OITC 24

Grille: ILT, No Custom Grille, 7/8", Traditional (2W4H), Square, Square**2: 3265 Fixed Sash Set****Frame Size:** 32 X 65**General Information:** Standard, Clad, Pine, 5", 3 11/16"**Exterior Color / Finish:** Painted, Standard Enduraclad, Iron Ore**Interior Color / Finish:** Unfinished Interior**Sash / Panel:** Square, Square, Standard, 1.46, 1.46, 1.46**Glass:** Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude**Performance Information:** U-Factor 0.28, SHGC 0.28, VLT 0.51, CPD PEL-N-1-59313-00001, Performance Class CW, PG 50, Calculated Positive DP

Rating 50, Calculated Negative DP Rating 50, FPA FL31312, STC 28, OITC 24


Grille: ILT, No Custom Grille, 7/8", Traditional (2W4H), Square, Square**Vertical Mull 1:** FactoryMull, Standard Joining Mullion, Frame To Frame Width- 0", Mull Design Pressure- 20**Wrapping Information:** Steady Set - Interior Install, Factory Applied, No Head Drip Cap, No Exterior Trim, 6-9/16", 7 7/8", Standard Four Sided Jamb Extension, Factory Applied, 2x6 Bracket, Manufacturer Recommended Clearance, Perimeter Length = 258".**Rough Opening:** 64 - 3/4" X 65 - 3/4"

21DRINST1000 - F - ADDER - Zip Tape Install Per LF - NCI

Qty 22

21DRINST0050 - A - Window Install Per LF - NCI - Whole House

Qty 22

Line #	Location:	Attributes			Item Price	Qty	Ext'd Price
105	Dining Room	Architect Reserve, Traditional, Direct Set, Architect Reserve, Traditional, Direct Set, Architect Reserve, Traditional, Direct Set, Architect Reserve, Traditional, Direct Set,			\$11,207.43	1	\$11,207.43
	Frame Radius = 61.586956"						
							
	Viewed From Exterior						
	PK # 2245	1: 3281 Fixed Frame Direct Set Frame Size: 32 X 81 General Information: Interior Glazed, Factory Assembled, Standard, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Glass: Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Performance Information: U-Factor 0.29, SHGC 0.29, VLT 0.55, CPD PEL-N-18-04210-00001, Performance Class AW, PG 60, Calculated Positive DP Rating 60, Calculated Negative DP Rating 60, FPA FL10354, STC 27, OITC 22 Grille: ILT, No Custom Grille, 7/8", Traditional (2W4H), Ogee, Ogee 2: 3281 Fixed Frame Direct Set Frame Size: 32 X 81 General Information: Interior Glazed, Factory Assembled, Standard, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Glass: Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Performance Information: U-Factor 0.29, SHGC 0.29, VLT 0.55, CPD PEL-N-18-04210-00001, Performance Class AW, PG 60, Calculated Positive DP Rating 60, Calculated Negative DP Rating 60, FPA FL10354, STC 27, OITC 22 Grille: ILT, No Custom Grille, 7/8", Traditional (2W4H), Ogee, Ogee 3: 3281 Fixed Frame Direct Set Frame Size: 32 X 81 General Information: Interior Glazed, Factory Assembled, Standard, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Glass: Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Performance Information: U-Factor 0.29, SHGC 0.29, VLT 0.55, CPD PEL-N-18-04210-00001, Performance Class AW, PG 60, Calculated Positive DP Rating 60, Calculated Negative DP Rating 60, FPA FL10354, STC 27, OITC 22 Grille: ILT, No Custom Grille, 7/8", Traditional (2W4H), Ogee, Ogee 4: 3237.88533 Fixed Frame Direct Set Partial Arch Head, Facing: Left Frame Size: 32 X 37 7/8 X 17 General Information: Interior Glazed, Standard, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Performance Information: U-Factor 0.29, SHGC 0.29, VLT 0.55, CPD PEL-N-18-04210-00001, Performance Class AW, PG 90, Calculated Positive DP Rating 90, Calculated Negative DP Rating 90, FPA FL10354 Grille: ILT, No Custom Grille, 7/8", Traditional (2W1H), Ogee, Ogee 5: 3240 Fixed Frame Direct Set Arch Head Frame Size: 32 X 40 X 37 7/8 General Information: Interior Glazed, Standard, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Performance Information: U-Factor 0.29, SHGC 0.29, VLT 0.55, CPD PEL-N-18-04210-00001, Performance Class AW, PG 90, Calculated Positive DP Rating 90, Calculated Negative DP Rating 90, FPA FL10354 Grille: ILT, No Custom Grille, 7/8", Traditional (2W1H), Ogee, Ogee 6: 3237.88533 Fixed Frame Direct Set Partial Arch Head, Facing: Right Frame Size: 32 X 37 7/8 X 17 General Information: Interior Glazed, Standard, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Performance Information: U-Factor 0.29, SHGC 0.29, VLT 0.55, CPD PEL-N-18-04210-00001, Performance Class AW, PG 90, Calculated Positive DP					

For more information regarding the finishing, maintenance, service and warranty of all Pella® products, visit the Pella® website at www.pella.com

Rating 90, Calculated Negative DP Rating 90, FPA FL10354

Grille: ILT, No Custom Grille, 7/8", Traditional (2W1H), Ogee, Ogee

Horizontal Mull 1: AlignedWith, 0.5"

Vertical Mull 1: FactoryMull, Standard Joining Mullion, Frame To Frame Width- 0", Mull Design Pressure- 20, Overall Thru Direction- Horizontal

Vertical Mull 2: FactoryMull, Reinforcing Plate, Frame To Frame Width- 0", Mull Design Pressure- 20, Overall Thru Direction- Horizontal

Vertical Mull 3: FactoryMull, Standard Joining Mullion, Frame To Frame Width- 0", Mull Design Pressure- 20, Overall Thru Direction- Horizontal

Vertical Mull 4: FactoryMull, Reinforcing Plate, Frame To Frame Width- 0", Mull Design Pressure- 20, Overall Thru Direction- Horizontal

Wrapping Information: Foldout Fins, Factory Applied, No Head Drip Cap, No Exterior Trim, 6-9/16", 7 7/8", Standard Four Sided Jamb Extension, Factory Applied, Manufacturer Recommended Clearance, Perimeter Length = 596".

Rough Opening: 96 - 3/4" X 40 - 3/4"

Customer Notes: COMPOSITE COMES IN (2) PIECES, FIELD MULL HORZ. WITH 1/2" ALUMINUM STRUCTURE 4 9/16" DEEP WITH (1) STEEL INSERT, FACTORY APPLIED 4 SIDED JAMB EXTENSION, OVERALL RO 122 1/2" X 96 3/4"

21STIN0500 - Adder - Wood Units 1/2 in Structural Mull per Mull

Qty 1

21STIN0100 - Labor to Structural Mull Window-Per Square Foot

Qty 82

21DRINST1000 - F - ADDER - Zip Tape Install Per LF - NCI

Qty 53

Line #	Location:	Attributes		
110	Head Drip Fin	Frame Radius = 61.588956"  PK # 2245 Viewed From Exterior 1: 3237.88533 Fixed Frame Direct Set Partial Arch Head, Facing: Left Frame Size: 32 X 37 7/8 X 17 General Information: Interior Glazed, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore 2: 3240 Fixed Frame Direct Set Arch Head Frame Size: 32 X 40 X 37 7/8 General Information: Interior Glazed, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore 3: 3237.88533 Fixed Frame Direct Set Partial Arch Head, Facing: Right Frame Size: 32 X 37 7/8 X 17 General Information: Interior Glazed, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Vertical Mull 1: FactoryMull, Reinforcing Plate, Frame To Frame Width- 0", Mull Design Pressure- 20 Vertical Mull 2: FactoryMull, Reinforcing Plate, Frame To Frame Width- 0", Mull Design Pressure- 20 Wrapping Information: Exterior Trim Options, Head Drip Fin, Perimeter Length = 241", Glazing Pressure = 90. Item Price \$297.05 Qty 1 Ext'd Price \$297.05		

Rough Opening: 96 - 3/4" X 40 - 3/4"

Line #	Location:	Attributes			
115	Dining Door	</			

Rough Opening: 96" X 96"

21DRINST0200 - C - 2 Panel Door per LF - NCI - Whole House

Qty 32

21DRINST1000 - F - ADDER - Zip Tape Install Per LF - NCI

Qty 32

Line #	Location:	Attributes		
120	Kitchen Sink	</		

Rough Opening: 58 - 3/4" X 53 - 3/4"

21DRINST0050 - A - Window Install Per LF - NCI - Whole House

Qty 19


21DRINST1000 - F - ADDER - Zip Tape Install Per LF - NCI

Qty 19

Line #	Location:	Attributes			
125	Hidden Pantry	</			

Rough Opening: 29 - 3/4" X 53 - 3/4"


21DRINST0050 - A - Window Install Per LF - NCI - Whole House	Qty	14
21DRINST1000 - F - ADDER - Zip Tape Install Per LF - NCI	Qty	14

Line #	Location:	Attributes				
130	Hidden P. Door		Pella Reserve, Contemporary Inswing Door, Contemporary,, Right, 37.875 X 95.5, Iron Ore	Item Price	Qty	Ext'd Price
				\$3,680.40	1	\$3,680.40
	PK # 2245	1: 3896 Right Inswing Door Frame Size: 37 7/8 X 95 1/2 General Information: Standard, Clad, Pine, 7 7/8", 6 9/16", Standard Sill, Black Finish Sill, Black Composite Threshold Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Sash / Panel: Square, Square, Standard Glass: Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Hardware Options: Spiere, Satin Nickel, Order Handle Set, Shipped Separate, Accessory Managed, Multipoint Lock, No Integrated Sensor Screen: No Screen Performance Information: U-Factor 0.28, SHGC 0.18, VLT 0.33, CPD PEL-N-218-08119-00001, Performance Class LC, PG 55, Calculated Positive DP Rating 55, Calculated Negative DP Rating 70, FPA FL14293, STC 31, OITC 25 Grille: ILT, No Custom Grille, 7/8", Traditional (2W4H), Square, Square Wrapping Information: Foldout Fins, Factory Applied, No Exterior Trim, 6-9/16", 7 7/8", Factory Applied, Manufacturer Recommended Clearance, Perimeter Length = 267".				
	Viewed From Exterior					

Rough Opening: 38 - 5/8" X 96"

21DRINST0100 - B - 1 Panel Door Per LF - NCI - Whole House	Qty	23
21DRINST1000 - F - ADDER - Zip Tape Install Per LF - NCI	Qty	23

Line #	Location:	Attributes	Item Price	Qty	Ext'd Price
135	Planning Room	Pella Reserve, Contemporary 2-Wide Casement, 58 X 53, Iron Ore	\$2,083.78	1	\$2,083.78



PK #
2245

Viewed From Exterior

1: 2953 Left Casement

Frame Size: 29 X 53

General Information: Crank Out, Standard, Clad, Pine, 5", 3 11/16"

Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore

Interior Color / Finish: Unfinished Interior

Sash / Panel: Square, Square, Standard, 1.46, 1.46, 1.46

Glass: Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude

Hardware Options: Wash Hinge Hardware, Saldo Fold-Away Crank, Champagne, No Window Opening Control Device, No Limited Opening Hardware, No Integrated Sensor, Shipped Separate, Accessory Managed

Screen: Full Screen, Champagne, InView™, Shipped Separate, Accessory Managed

Performance Information: U-Factor 0.29, SHGC 0.27, VLT 0.51, CPD PEL-N-11-24313-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, FPA FL31311, STC 26, OITC 23, Egress Meets minimum clear opening and 5.7 sq.ft

Grille: No Grille,

2: 2953 Right Casement

Frame Size: 29 X 53

General Information: Crank Out, Standard, Clad, Pine, 5", 3 11/16"

Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore

Interior Color / Finish: Unfinished Interior

Sash / Panel: Square, Square, Standard, 1.46, 1.46, 1.46

Glass: Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude

Hardware Options: Wash Hinge Hardware, Saldo Fold-Away Crank, Champagne, No Window Opening Control Device, No Limited Opening Hardware, No Integrated Sensor, Shipped Separate, Accessory Managed

Screen: Full Screen, Champagne, InView™, Shipped Separate, Accessory Managed

Performance Information: U-Factor 0.29, SHGC 0.27, VLT 0.51, CPD PEL-N-11-24313-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, FPA FL31311, STC 26, OITC 23, Egress Meets minimum clear opening and 5.7 sq.ft

Grille: No Grille,

Vertical Mull 1: FactoryMull, Standard Joining Mullion, Frame To Frame Width- 0", Mull Design Pressure- 20

Wrapping Information: Steady Set - Interior Install, Factory Applied, No Head Drip Cap, No Exterior Trim, 6-9/16", 7 7/8", Standard Four Sided Jamb Extension, Factory Applied, 2x6 Bracket, Manufacturer Recommended Clearance, Perimeter Length = 222".

Rough Opening: 58 - 3/4" X 53 - 3/4"

21DRINST0050 - A - Window Install Per LF - NCI - Whole House

Qty 19

21DRINST1000 - F - ADDER - Zip Tape Install Per LF - NCI

Qty 19

Line #	Location:	Attributes		
140	Garage Left	59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245 59" 29" 58" 29" Viewed From Exterior PK # 2245		

Line #	Location:	Attributes		
145	Bed 2	</		

Rough Opening: 64 - 3/4" X 65 - 3/4"

Customer Notes: QUOTED WITH W.O.C.D. FOR FALL PROTECTION


QUOTED OPERABLE CM DUE TO EGRESS

21DRINST0050 - A - Window Install Per LF - NCI - Whole House

Qty 22

21DRINST1000 - F - ADDER - Zip Tape Install Per LF - NCI

Qty 22

Line #	Location:	Attributes					
150	Sitting Room	Pella Reserve, Contemporary 2-Wide Sash Set, 50 X 71, Iron Ore			Item Price	Qty	Ext'd Price
					\$2,488.36	1	\$2,488.36
							
	Viewed From Exterior						
	PK # 2245						
		1: 2571 Fixed Sash Set Frame Size: 25 X 71 General Information: Standard, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Sash / Panel: Square, Square, Standard, 1.46, 1.46, 1.46 Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Performance Information: U-Factor 0.28, SHGC 0.28, VLT 0.51, CPD PEL-N-1-59313-00001, Performance Class CW, PG 35, Calculated Positive DP Rating 35, Calculated Negative DP Rating 35, FPA FL31312 Grille: ILT, No Custom Grille, 7/8", Traditional (2W4H), Square, Square 2: 2571 Fixed Sash Set Frame Size: 25 X 71 General Information: Standard, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Sash / Panel: Square, Square, Standard, 1.46, 1.46, 1.46 Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Performance Information: U-Factor 0.28, SHGC 0.28, VLT 0.51, CPD PEL-N-1-59313-00001, Performance Class CW, PG 35, Calculated Positive DP Rating 35, Calculated Negative DP Rating 35, FPA FL31312 Grille: ILT, No Custom Grille, 7/8", Traditional (2W4H), Square, Square Vertical Mull 1: FactoryMull, Standard Joining Mullion, Frame To Frame Width- 0", Mull Design Pressure- 20 Wrapping Information: Steady Set - Interior Install, Factory Applied, No Head Drip Cap, No Exterior Trim, 6-9/16", 7 7/8", Standard Four Sided Jamb Extension, Factory Applied, 2x6 Bracket, Manufacturer Recommended Clearance, Perimeter Length = 242".					
	Rough Opening: 50 - 3/4" X 71 - 3/4"						
		21DRINST0050 - A - Window Install Per LF - NCI - Whole House			Qty	21	
		21DRINST1000 - F - ADDER - Zip Tape Install Per LF - NCI			Qty	21	

Line #	Location:	Attributes		
155	Bed 3	Pella Reserve, Contemporary 2-Wide Casement, 64 X 65, Iron Ore	Item Price	Qty
			\$3,335.98	1
				Ext'd Price
				\$3,335.98

Viewed From Exterior

PK #
2245

1: 3265 Left Casement
Frame Size: 32 X 65
General Information: Crank Out, Standard, Clad, Pine, 5", 3 11/16"
Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore
Interior Color / Finish: Unfinished Interior
Sash / Panel: Square, Square, Standard, 1.46, 1.46, 1.46
Glass: Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude
Hardware Options: Wash Hinge Hardware, Saldo Fold-Away Crank, Champagne, WOCD (ASTM F2090), No Limited Opening Hardware, No Integrated Sensor, Shipped Separate, Accessory Managed
Screen: Full Screen, Champagne, InView™, Shipped Separate, Accessory Managed
Performance Information: U-Factor 0.29, SHGC 0.25, VLT 0.46, CPD PEL-N-11-24315-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, FPA FL31311, STC 26, OITC 23, Egress Meets minimum clear opening and 5.7 sq.ft
Grille: ILT, No Custom Grille, 7/8", Traditional (2W4H), Square, Square

2: 3265 Right Casement
Frame Size: 32 X 65
General Information: Crank Out, Standard, Clad, Pine, 5", 3 11/16"
Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore
Interior Color / Finish: Unfinished Interior
Sash / Panel: Square, Square, Standard, 1.46, 1.46, 1.46
Glass: Insulated Dual Tempered Low-E Advanced Low-E Insulating Glass Argon Non High Altitude
Hardware Options: Wash Hinge Hardware, Saldo Fold-Away Crank, Champagne, WOCD (ASTM F2090), No Limited Opening Hardware, No Integrated Sensor, Shipped Separate, Accessory Managed
Screen: Full Screen, Champagne, InView™, Shipped Separate, Accessory Managed
Performance Information: U-Factor 0.29, SHGC 0.25, VLT 0.46, CPD PEL-N-11-24315-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, FPA FL31311, STC 26, OITC 23, Egress Meets minimum clear opening and 5.7 sq.ft
Grille: ILT, No Custom Grille, 7/8", Traditional (2W4H), Square, Square
Vertical Mull 1: FactoryMull, Standard Joining Mullion, Frame To Frame Width- 0", Mull Design Pressure- 20
Wrapping Information: Steady Set - Interior Install, Factory Applied, No Head Drip Cap, No Exterior Trim, 6-9/16", 7 7/8", Standard Four Sided Jamb Extension, Factory Applied, 2x6 Bracket, Manufacturer Recommended Clearance, Perimeter Length = 258".

Rough Opening: 64 - 3/4" X 65 - 3/4"

Customer Notes: QUOTED WITH W.O.C.D. FOR FALL PROTECTION


QUOTED OPERABLE CM DUE TO EGRESS


21DRINST0050 - A - Window Install Per LF - NCI - Whole House

Qty 22

21DRINST1000 - F - ADDER - Zip Tape Install Per LF - NCI

Qty 22

Line #	Location:	Attributes		
160	Bed 4	Pella Reserve, Contemporary 2-Wide Sash Set, 58 X 53, Iron Ore	Item Price	Qty
			\$1,627.70	1
				Ext'd Price
				\$1,627.70
	 PK # 2245 Viewed From Exterior	1: 2953 Fixed Sash Set Frame Size: 29 X 53 General Information: Standard, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Sash / Panel: Square, Square, Standard, 1.46, 1.46, 1.46 Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Performance Information: U-Factor 0.27, SHGC 0.30, VLT 0.57, CPD PEL-N-1-59311-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, FPA FL31312 Grille: No Grille, 2: 2953 Fixed Sash Set Frame Size: 29 X 53 General Information: Standard, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Sash / Panel: Square, Square, Standard, 1.46, 1.46, 1.46 Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Performance Information: U-Factor 0.27, SHGC 0.30, VLT 0.57, CPD PEL-N-1-59311-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, FPA FL31312 Grille: No Grille, Vertical Mull 1: FactoryMull, Standard Joining Mullion, Frame To Frame Width- 0", Mull Design Pressure- 20 Wrapping Information: Steady Set - Interior Install, Factory Applied, No Head Drip Cap, No Exterior Trim, 6-9/16", 7 7/8", Standard Four Sided Jamb Extension, Factory Applied, 2x6 Bracket, Manufacturer Recommended Clearance, Perimeter Length = 222".		
	Rough Opening: 58 - 3/4" X 53 - 3/4"			
	21DRINST0050 - A - Window Install Per LF - NCI - Whole House	Qty	19	
	21DRINST1000 - F - ADDER - Zip Tape Install Per LF - NCI	Qty	19	

Line #	Location:	Attributes						
165	Bed 4	 Viewed From Exterior PK # 2245 Pella Reserve, Contemporary Casement Right, 29 X 41, Iron Ore 1: 2941 Right Casement Frame Size: 29 X 41 General Information: Crank Out, Standard, Clad, Pine, 5", 3 11/16" Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Interior Color / Finish: Unfinished Interior Sash / Panel: Square, Square, Standard, 1.46, 1.46, 1.46 Glass: Insulated Dual Low-E Advanced Low-E Insulating Glass Argon Non High Altitude Hardware Options: Side Pivot Hardware, Saldo Fold-Away Crank, Champagne, No Window Opening Control Device, No Limited Opening Hardware, No Integrated Sensor, Shipped Separate, Accessory Managed Screen: Full Screen, Champagne, InView™ , Shipped Separate, Accessory Managed Performance Information: U-Factor 0.29, SHGC 0.27, VLT 0.51, CPD PEL-N-11-24313-00001, Performance Class CW, PG 50, Calculated Positive DP Rating 50, Calculated Negative DP Rating 50, FPA FL31311, STC 26, OITC 23, Clear Opening Width 24.625, Clear Opening Height 36.875, Clear Opening Area 6.305881, Egress With optional side pivot hardware, meets minimum clear opening and 5.7 sq.ft Grille: No Grille, Wrapping Information: Steady Set - Interior Install, Factory Applied, No Exterior Trim, 6-9/16", 7 7/8", Standard Four Sided Jamb Extension, Factory Applied, 2x6 Bracket, Manufacturer Recommended Clearance, Perimeter Length = 140". <table><tr><th>Item Price</th><th>Qty</th><th>Ext'd Price</th></tr><tr><td>\$896.25</td><td>1</td><td>\$896.25</td></tr></table>	Item Price	Qty	Ext'd Price	\$896.25	1	\$896.25
Item Price	Qty	Ext'd Price						
\$896.25	1	\$896.25						

Viewed From Exterior

Rough Opening: 29 - 3/4" X 41 - 3/4"

Customer Notes: QUOTED WITH SIDE PIVOT HARDWARE FOR EGRESS

21DRINST0050 - A - Window Install Per LF - NCI - Whole House

Qty 12

21DRINST1000 - F - ADDER - Zip Tape Install Per LF - NCI

Qty 12

Line #	Location:	Attributes		
170	Head Drip Flashing	Head Drip Flashing, Length: 192, Iron Ore 1: Accessory Frame Size: 1 X 1 General Information: Head Drip Flashing Exterior Color / Finish: Painted, Standard Enduraclad, Iron Ore Wrapping Information: Perimeter Length = 0". PK # 2245 Item Price \$83.25 Qty 12 Ext'd Price \$999.00		
Viewed From Exterior				

Viewed From Exterior

Line #	Location:	Attributes			
175	Keyed Alike	058F0001 - Pella Hinged Door SmartKey, Key Lock, Nickel Faced	Item Price	Qty	Ext'd Price
			\$25.39	4	\$101.56
					
1: Pella Parts Catalog - Templates Search					
Pella Parts Selector: Part Number, 058F0001, Hinged Door SmartKey, Key Lock, Nickel Faced, 058F0001,					
PK #					
2245					
Viewed From Exterior					

Line #	Location:	Attributes			
180	Lift Rental	21NCI0200 - Lift Charge Per Day	Item Price	Qty	Ext'd Price
			\$1,050.00	1	\$1,050.00

Line #	Location:	Attributes			
185	Shop Drawings	SHOPDRAWINGS - Shop Drawings	Item Price	Qty	Ext'd Price
			\$1,390.00	1	\$1,390.00

Line #	Location:	Attributes	Item Price	Qty	Ext'd Price
190	Install Package	21NCI0300 - Install Package	\$6,250.00	1	\$6,250.00

Thank You For Purchasing Pella® Products

PELLA WARRANTY:

Pella products are covered by Pella's limited warranties in effect at the time of sale. All applicable product warranties are incorporated into and become a part of this contract. Please see the warranties for complete details, taking special note of the two important notice sections regarding installation of Pella products and proper management of moisture within the wall system. Neither Pella Corporation nor the Seller will be bound by any other warranty unless specifically set out in this contract. However, Pella Corporation will not be liable for branch warranties which create obligations in addition to or obligations which are inconsistent with Pella written warranties.

Clear opening (egress) information does not take into consideration the addition of a Rolscreen [or any other accessory] to the product. You should consult your local building code to ensure your Pella products meet local egress requirements.

Per the manufacturer's limited warranty, unfinished mahogany exterior windows and doors must be finished upon receipt prior to installing and refinished annually, thereafter. Variations in wood grain, color, texture or natural characteristics are not covered under the limited warranty.

Notice of Collection of Personal Information: We may collect your personal information when you interact with us. Under the California Consumer Privacy Act (CCPA), California residents have specific rights to request this information, request to delete this information, and opt out of the sharing or sale of this information to third parties. To learn more about our collection practices and your rights under the CCPA please visit our link <https://www.pella.com/california-rights-policy/> at pella.com.

ARBITRATION AND CLASS ACTION WAIVER ("ARBITRATION AGREEMENT")

YOU and Pella and its subsidiaries and the Pella Branded Distributor AGREE TO ARBITRATE DISPUTES ARISING OUT OF OR RELATING TO YOUR PELLA PRODUCTS (INCLUDES PELLA GOODS AND PELLA SERVICES) AND WAIVE THE RIGHT TO HAVE A COURT OR JURY DECIDE DISPUTES. YOU WAIVE ALL RIGHTS TO PROCEED AS A MEMBER OR REPRESENTATIVE OF A CLASS ACTION, INCLUDING CLASS ARBITRATION, REGARDING DISPUTES ARISING OUT OF OR RELATING TO YOUR PELLA PRODUCTS. You may opt out of this Arbitration Agreement by providing notice to Pella no later than ninety (90) calendar days from the date You purchased or otherwise took ownership of Your Pella Goods. To opt out, You must send notice by e-mail to pellawebsupport@pella.com, with the subject line: "Arbitration Opt Out" or by calling (877) 473-5527. Opting out of the Arbitration Agreement will not affect the coverage provided by any applicable limited warranty pertaining to Your Pella Products. For complete information, including the full terms and conditions of this Arbitration Agreement, which are incorporated herein by reference, please visit www.pella.com/arbitration or e-mail to pellawebsupport@pella.com, with the subject line: "Arbitration Details" or call (877) 473-5527. D'ARBITRAGE ET RENONCIATION AU RECOURS COLLECTIF ("convention d'arbitrage") EN FRANÇAIS SEE PELLA.COM/ARBITRATION. DE ARBITRAJE Y RENUNCIA COLECTIVA ("acuerdo de arbitraje") EN ESPAÑOL VER PELLA.COM/ARBITRATION.

Seller shall not be held liable for failure or delay in the performance of its obligations under this Agreement, if such performance is hindered or delayed by the occurrence of an act or event beyond the Seller's reasonable control (force majeure event), including but not limited to earthquakes, unusually severe weather and other Acts of God, fire, strikes and labor unrest, epidemics, riots, war, civil unrest, and government interventions. Seller shall give timely notice of a force majeure event and take such reasonable action to mitigate the impacts of such an event.

Product Performance Information:

U-Factor, Solar Heat Gain Coefficient (SHGC), and Visible Light Transmittance (VLT) are certified by the National Fenestration Rating Council (NFRC). Manufacturer stipulates that these ratings conform to applicable NFRC procedures for determining whole product performance. NFRC ratings are determined for a fixed set of environmental conditions and a specific product size. NFRC does not recommend any products and does not warrant the suitability of any product for any specific use.

Design Pressure (DP), Performance Class, and Performance Grade (PG) are certified by a third party organization. The certification requires the performance of at least one product of the product line to be tested in accordance with the applicable performance standards and verified by an independent party. The certification indicates that the product(s) of the product line passed the applicable tests. The certification does not apply to mulled and/or product combinations unless noted. Actual product results will vary based on environmental conditions, installation, and other construction practices and change over the product's life.

For more performance information along with information on Florida Product Approval System (FPAS) Number and Texas Dept. of Insurance (TDI) number go to www.pella.com/performance.

Including during the construction period, casement windows should never be left open and unlocked for prolonged periods or during high wind conditions to avoid sash detachment/damage.

Actual sizes tested for documented STC and OITC ratings may vary from the ASTM E 1425 sizes to better represent Pella Product Offering. STC and OITC ratings shown may be conservatively based on products tested with thinner panes of glass. STC and OITC ratings may be from test results from an equivalent product.

New Construction :**PAYMENT TERMS:**

WARRANTY: Pella® products are covered by Pella's limited warranties in effect at the time of sale. All applicable product warranties are incorporated into and become a part of this contract. Please see the warranties for complete details. Neither Pella Corporation nor Pella Products of Omaha and Lincoln will be bound by any other warranty. Please be aware that product which is not fully paid for is not covered by the warranty.

RETURN FEES: A 50% Fee will be charged for all items cancelled by the customer after the Last Revision Date. Your sales representative can provide you with information related to Last Revision Dates.

Initials: _____

DAMAGED PRODUCT: Product delivered to jobsite that is received damaged, must be reported to our Trade Project Coordinator Dept within 10 calendar days of date of delivery. Damaged product reported after 10 calendar days of delivery will be considered jobsite damage and will be billable by our company.

MISSING PRODUCT: Product delivered by our company and found to be missing from the jobsite must be reported to our Trade Project Coordinator Dept within 5 calendar days of the delivery date, or the product will be considered stolen or disposed of at the jobsite and replacement product will be billable by our company.

Remodeling or Replacement :**PAYMENT TERMS:**

Orders placed by homeowners require a 50% down payment in advance of the order being placed. For remodeling or replacement jobs installed by our company, the customer can withhold a maximum of 5% of the contract price until the job is completed to the customer's satisfaction should any issues arise during completion of the work. Service parts ordered by our company which are not covered by the Pella warranty (see WARRANTY paragraph) must be paid for in full prior to scheduling or commencement of any service work by our company.

WARRANTY: Pella® products are covered by Pella's limited warranties in effect at the time of sale. All applicable product warranties are incorporated into and become a part of this contract. Please see the warranties for complete details. Neither Pella Corporation nor Pella Products of Omaha and Lincoln will be bound by any other warranty. Please be aware that product which is not fully paid for is not covered by the warranty.

RETURN FEES: A 50% Fee will be charged for all items cancelled by the customer after the Last Revision Date. Your salesrep can provide you with information related to Last Revision Dates.

Initials: _____

PREFINISHING: For remodeling or replacement orders placed by homeowners, Pella Products of Omaha and Lincoln offers painting & staining applications prior to installation of our products. The stain color sample is only a general representation of the final product. Variations in different batches of stain along with natural differences in absorption rates, grain color, and characteristics of veneers and solid woods can and do affect the final wood color. Such variations will be considered normal and not cause for replacement. We will not accept returns based upon stains not matching samples, and will not issue monetary credit for any variation in final stain color from the sample.

Stain Color _____

Initials: _____

WINDOW TREATMENTS: Your new windows are custom made for your opening. Pella manufactures it's product to be of the highest quality in order that your new windows will be more energy efficient. Every Manufacturers frame is unique in profile and fit. It is possible that your existing interior mounted blinds or shades will no longer fit inside our frames. It is also possible that your existing shutters may not fit on your new energy efficient windows. Pella will not be responsible for these items and will not issue monetary credit or pay for any replacement blind or shades necessitated by the replacement of your windows.

Initials: _____

SECURITY SYSTEMS: During installation of Buyer's new windows and/or doors, security system wires and/or hardware may be damaged. Buyer is responsible for the coordination of their security system being disconnected prior to installation and reconnected after installation with a third party. Buyer acknowledges that Pella will not be responsible for these items and will not issue monetary credit or pay for any replacement of security hardware necessitated by the replacement of Buyer's windows.

Initials: _____

INSTALLATION IN EIFS/STUCCO: During installation of Buyer's new windows and/or doors in homes with EIFS or Stucco, Pella Windows and Doors will cut back the EIFS or Stucco to install

For more information regarding the finishing, maintenance, service and warranty of all Pella® products, visit the Pella® website at www.pella.com

Buyer's new windows and/or doors. Buyer is responsible for the coordination of EIFS or Stucco work after installation of windows and/or doors through a 3rd party. Buyer is also responsible for coordinating the caulking of windows after completion of EIFS or Stucco work through a 3rd party. Buyer acknowledges that Pella will not be responsible for these items and will not issue monetary credit or pay for any EIFS work, Stucco work, or caulking associated with these types of installs necessitated by the replacement of Buyer's windows.

Initials: _____

RIGHT TO RENOVATE: If your home was built prior to 1978, a lead test must be performed by the contractor prior to Pella performing any installation services.

BUILDING PERMITS: It is the responsibility of the contractor to pull any and all permits necessary prior to Pella performing any installation services.

DAMAGED PRODUCT: Product delivered to jobsite that is received damaged, must be reported to our Trade Project Coordinator Dept within 10 calendar days of date of delivery. Damaged product reported after 10 calendar days of delivery will be considered jobsite damage and will be billable by our company.

MISSING PRODUCT: Product delivered by our company and found to be missing from the jobsite must be reported to our Trade Project Coordinator Dept within 5 calendar days of the delivery date, or the product will be considered stolen or disposed of at the jobsite and replacement product will be billable by our company.

Invoices will be submitted to the customer upon installation with the deposit applied first, with invoices for installations due in 30 days or when the project is substantially complete. Substantial completion is defined at the point when work is nearly complete, and the building can be occupied and used as intended. For remodeling or replacement jobs installed by our company, the customer can withhold to a maximum of 5% of the contract price until the job is completed to the customer's satisfaction should any issues arise during completion of the work. Service parts ordered by our company which are not covered by the Pella warranty (see WARRANTY paragraph) must be paid for in full prior to scheduling or commencement of any service work by our company.

Initials: _____

Each multi-panel and multi-slide system needs an approved design analysis and Pella Corporation stamped shop drawings signed off on prior to ordering. Since the products do not have an air and water performance rating, both overhangs and water managing patios or sloping are required. All multi-slide systems must have a minimum overhang of 50% of the height of the door for weather protection. All labor, product, and factory warranties will be voided without the minimum overhang requirements. Pella Windows & Doors of Omaha & Lincoln recommends a level rough opening for optimal performance. If the opening isn't level or doesn't include a slope away from the system, warranty exclusions will be applied.

Initials: _____

☐ **Project Checklist has been reviewed**_____
Customer Name (Please print)_____
Pella Sales Rep Name (Please print)_____
Customer Signature_____
Pella Sales Rep Signature_____
Date_____
Date_____
Credit Card Approval Signature**Order Totals**

Taxable Subtotal	\$95,666.37
Sales Tax @ 0%	\$0.00
Non-taxable Subtotal	\$14,923.05
Total	\$110,589.42
Deposit Received	\$0.00
Amount Due	\$110,589.42